

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

Technical Data:

Material:

- Contact(metal housing): Brass (CuZn)
- Terminal screw: Steel galvanized and chromotize or Nickel plated or Tin pltd(standard)(optian)
- Wire guard: Stainless steel
- Surface of solder tail: tin plated
- Insulator body(housing): Polyamide(Glass filled)(UL94V-0)

Electrical


- Voltage rating: 250VAC
- Current rating: 16 Amps/way max
- Contact resistance: 20mΩ(max)
- Insulation resistance: 5000MΩ/1000V
- Withsanding Voltage: 2000VAC(lmim) Test time=60sec/1pcs
- Wire range: 14-22AWG

Mechanical:

- Torque: 4kg-cm/M3
- Operating temperature: -33°C to +120°C
- Soldering ability: 95%coverage(min)
Test temperature= 230°C±10°C
Test time= 4sec±0.5sec
- Soldering reliability:
Test temperature= 250°C±10°C
5 seconds max

Safety approval defa:

POLE	3P	
A	NX7.5	22.6
B	(N-1) X7.5	15.0



杰科电子有限公司

JIE KE ELECTRONICS CO., LTD.

PART. NAME: JK300R-750 3P				TITLE:	
PART. NO.:				DWG NAME: △	
APPROVED BY	CHECKED BY	DESIGNED BY	DRAWN BY	CUSTOM NO.:	Tolence x. ±0.50 x.x ±0.30 x.xx ±0.10 xx° ±1°
岑杰	孙学峰	杨丽霞	杨丽霞	UNITS: mm	
				SCALE: 4/1	
				REVISION: B1	