

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

Technical Data:

Material:

- o Contact(metal housing): Zinc Die Casting or Brass Machined(option)
- o Terminal screw: Steel galvanized and achromatized or Nickel plated or Tin plated(standard)(option)
- o Solder Pin: Brass with Tin plated
- o Insulator body(housing): Polyamide(Glass filled)(UL 94V-0)

Electrical


- Voltage rating: 300VAC
- Current rating: 10 Amps/way max
- Contact resistance: 20mΩ(max)
- Insulation resistance: 5000MΩ/1000V
- Withstanding Voltage: 2000VAC(1min) Test time=60sec/1pcs
- Wire range: 16-26AWG

Mechanical:

- Torque: 4kgf.cm/M2.5
- Operating temperature: -33°C to +120°C
- Soldering reliability: Test temperature= 250°C±10°C 5 seconds max

Safety approval deta:

POLE	2P	
A	NX5.0	10.0
B	(N-1) X5.0	5.0



**杰科电子有限公司**  
JIE KE ELECTRONICS CO., LTD.

PART NAME: JK127-500 2P

TITLE:

PART NO.:

DWG NAME:

APPROVED BY

CHECKED BY

DESIGNED BY

DRAWN BY

CUSTOM NO.:

Tolerance

**岑杰**

**孙学丰**

UNITS: mm  
SCALE: 4/1  
REVISION: B4

x ±0.50  
x.x ±0.30  
x.xx ±0.10  
xx° ±1°